



SAFETY DATA SHEET
SUPERCOLDMASTER ANTIFREEZE

Page 1

Issued: 12/11/2002

Revision No: 3

Comma Oil & Chemicals Ltd.

Lower Range Road

Gravesend

Kent

DA12 2QX

Tel: +44 01474 564311

Fax: +44 01474 333000

1. IDENTIFICATION OF THE SUBSTANCE / PREPARATION AND OF THE COMPANY / UNDERTAKING

Product name: SUPERCOLDMASTER ANTIFREEZE

Product code: SCA***L

Use / description of product: Harmful. Liquid.

2. COMPOSITION / INFORMATION ON INGREDIENTS

Ingredient 1: ETHANDIOL >90%

CAS: 107-21-1

[Xn] R22;

Ingredient 2: DI ETHYLENE GLYCOL <10%

CAS: 111-46-6

[Xn] R22;

Contains: The above information refers only to ingredients that are hazardous.

3. HAZARDS IDENTIFICATION

Main hazards: Harmful if swallowed.

4. FIRST AID MEASURES (SYMPTOMS)

Skin contact: There may be irritation and redness at the site of contact.

Eye contact: There may be irritation and redness.

Ingestion: Nausea and stomach pain may occur. There may be vomiting. There may be loss of consciousness. Convulsions may occur.

Inhalation: Exposure may cause coughing or wheezing. There may be congestion of the lungs causing severe shortness of breath. There may be loss of consciousness. Convulsions may occur.

4. FIRST AID MEASURES (ACTION)

Skin contact: Remove all contaminated clothes and footwear immediately unless stuck to skin. Drench the affected skin with running water for 10 minutes or longer if substance is still on skin. Transfer to hospital if there are burns or symptoms of poisoning.

Eye contact: Bathe the eye with running water for 15 minutes. Transfer to hospital for specialist examination.

Ingestion: Do not induce vomiting. If conscious, give 1 pint of water to drink immediately. If unconscious, check for breathing and apply artificial respiration if necessary. If unconscious and breathing is OK, place in the recovery position. Transfer to hospital

[cont...]

SAFETY DATA SHEET
SUPERCOLDMASTER ANTIFREEZE

as soon as possible.

Inhalation: Remove casualty from exposure ensuring one's own safety whilst doing so. If unconscious, check for breathing and apply artificial respiration if necessary. If unconscious and breathing is OK, place in the recovery position. If conscious, ensure the casualty sits or lies down. If breathing becomes bubbly, have the casualty sit and provide oxygen if available. Transfer to hospital as soon as possible.

5. FIRE-FIGHTING MEASURES

Extinguishing media: Carbon dioxide. Alcohol or polymer foam. Dry chemical powder.

Exposure hazards: In combustion emits toxic fumes.

Protection of fire-fighters: Wear self-contained breathing apparatus. Wear protective clothing to prevent contact with skin and eyes.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions: Mark out the contaminated area with signs and prevent access to unauthorised personnel. Turn leaking containers leak-side up to prevent the escape of liquid.

Environmental precautions: Do not discharge into drains or rivers. Contain the spillage using bunding.

Clean-up procedures: Absorb into dry earth or sand. If inside, transfer outside of building in suitable containers. For small spills, absorb on to paper and allow to evaporate in a fume cupboard. Wash the spillage site with large amounts of water.

7. HANDLING AND STORAGE

Handling requirements: Ensure there is sufficient ventilation of the area. Avoid direct contact with the substance.

Storage conditions: Store in cool, well ventilated area. Keep container tightly closed.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Engineering measures: Ensure there is sufficient ventilation of the area.

Respiratory protection: Self-contained breathing apparatus must be available in case of emergency.

Hand protection: Butyl gloves. Rubber gloves. Neoprene gloves. PVC gloves.

Eye protection: Safety goggles.

Skin protection: Protective clothing with elasticated cuffs and closed neck. Boots made of PVC. Ensure safety shower is to hand.

9. PHYSICAL AND CHEMICAL PROPERTIES

State: Liquid

Colour: Blue

Odour: Odourless

Viscosity: Viscous

Oxidising: Non-oxidising (by EC criteria)

Solubility in water: Miscible

Also soluble in: Acetone. Ethanol.

Boiling point/range°C: > 160

Flash point°C: > 100

Autoflammability°C: 400

Relative density: 1.127 @ 20 C

10. STABILITY AND REACTIVITY

Stability: Stable under normal conditions.

Conditions to avoid: Moist air. Flames.

Materials to avoid: Strong oxidising agents. Acids.

11. TOXICOLOGICAL INFORMATION

12. ECOLOGICAL INFORMATION

13. DISPOSAL CONSIDERATIONS

Waste disposal: Mix or dissolve with a combustible material and burn in a chemical incinerator equipped with afterburners and scrubbers.

Disposal of packaging Dispose of as normal industrial waste.

NB: The user's attention is drawn to the possible existence of regional or national regulations regarding disposal.

14. TRANSPORT INFORMATION

ADR / RID

IMDG / IMO

IATA / ICAO

15. REGULATORY INFORMATION

Hazard symbols: Harmful.



Risk phrases: R22: Harmful if swallowed.

Safety phrases: S2: Keep out of the reach of children.

S46: If swallowed, seek medical advice immediately and show this container or label.

Note: The regulatory information given above only indicates the principal regulations specifically applicable to the product described in the safety data sheet. The user's attention is drawn to the possible existence of additional provisions which complete these regulations. Refer to all applicable national, international and local regulations or provisions.

16. ADDITIONAL INFORMATION

Risk phrases used in s.2: R22: Harmful if swallowed.

Legal disclaimer: The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. This company shall not be held liable for any damage resulting from handling or from contact with the above product.